



ADVANTAGES

- Available with three different pleat packs (media surface)
- Compact design concept

Application	HEPA filter for standard applications
Type	Box Filter
Frame	Galvanised steel
Gasket	Polyurethane, endless foamed
Media	Glass fiber
Separator	Hot-melt
Sealant	Polyurethane
Max. final pressure drop	800 Pa
Max airflow	Nominal flow rate (if not, efficiency drops)
Temperature max	70°C
RH. max	100%
Comment	Remarks: All filters scan tested acc. EN 1822 Other options available: Galvanized frame

Model Name	EN1822	Dimensions WxHxD (mm)	Air Flow/pressure drop (m³/h/Pa)	Media area (m²)	Weight (kg)
CET13-305x305x292-PR	H13	305x305x292	625/250	5,7	5,63
CET13-305x610x292-PR	H13	305x610x292	1260/250	11,7	8,29
CET13-610x610x292-PR	H13	610x610x292	2535/250	23,5	13
CET14-305x305x292-PR-S	H14	305x305x292	515/250	5,7	5,63
CET14-305x610x292-PR-S	H14	305x610x292	1045/250	13	8,29
CET14-610x610x292-PR	H14	610x610x292	2100/250	26	13
CET14-305x610x292-PR-SH	H14	305x610x292	1045/250	11,7	8,29
CET14-610x610x292-PR-SH	H14	610x610x292	2100/250	26	13

Pressure drop: ±10%

Type -P = 1PU gasket placed upstream

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice.

2020-03-09