



ADVANTAGES

- Flexible in the dimensions
- Lightweight and installation friendly
- Compliant to VDI 6022
- Scannable
- Rated airflow capacity of up to 3400 m³/h 610x610 (H13)
- Halogen free
- Low outgassing

Application	HEPA-Filter for high air flows
Type	Close Pleated Filter
Frame	ABS
Gasket	Polyurethane, endless foamed
Media	Glass fiber
Separator	Hot-melt
Sealant	Polyurethane
Max. final pressure drop	1000 Pa
Temperature max	70°C
RH. max	100%
Comment	Remarks: All filters scan-tested acc. EN 1822:2009

Model Name	EN1822	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Media area (m ²)	Weight (kg)
DG13-305x610x292-P-0-I	H13	305x610x292	1600/250	18,5	8,5
DG13-610x610x292-P-0-I	H13	610x610x292	3400/250	37,8	12
DG13-762x610x292-P-0-I	H13	762x610x292	4250/250	48,5	15,5
DG14-305x610x292-P-0-I	H14	305x610x292	1350/290	18,5	8,5
DG14-610x610x292-P-0-I	H14	610x610x292	3200/290	39,6	12,0
DG14-762x610x292-P-0-I	H14	762x610x292	4100/290	48,5	15,5

Other dimensions on demand

Pressure drop: +/- 15%

Type P = gasket on in let air side

Type I = filter with handle and foil

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice.

2020-03-11