



ADVANTAGES

- Incinerable
- Compact HEPA filter with header frame

Application	High efficiency final filtration in air conditioning systems and industrial processes
Type	V-Bank Filter
Frame	ABS; header frame, 25mm
Gasket	Polyurethane, endless foamed; Flat gasket
Media	Glass fiber
Separator	Hot-melt
Sealant	Polyurethane
Max. final pressure drop	500 Pa
Temperature max	70°C
RH. max	100%
Comment	Remarks: All filter scan-tested acc. EN 1822:2009 and individually packed in PE-foil. Other editions on request Variant: Filter also available with flat gasket

Model Name	EN1822	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Media area (m ²)	Weight (kg)
VGHF11-592x287x292-0P	E11	592x287x292	1350/165	13	3
VGHF11-592x490x292-0P	E11	592x490x292	2450/165	23	4.5
VGHF11-592x592x292-0P	E11	592x592x292	3000/165	28	6
VGHF11-592x287x292-F	E11	592x287x292	1350/165	13	3,5
VGHF11-592x490x292-F	E11	592x490x292	2450/165	23	6
VGHF11-592x592x292-F	E11	592x592x292	3000/165	28	10
VGHF13-592x287x292-0P	H13	592x287x292	1350/250	13	3
VGHF13-592x490x292-0P	H13	592x490x292	2450/250	23	5.2
VGHF13-592x592x292-0P	H13	592x592x292	3000/250	28	6
VGHF13-592x287x292-F	H13	592x287x292	1350/250	13	3,5
VGHF13-592x490x292-F	H13	592x490x292	2450/250	23	6
VGHF13-592x592x292-F	H13	592x592x292	3000/250	28	10

Pressure drop: ± 10%

Type: -0P = gasket placed downstream, -F = gasket placed upstream

Gasket: P = Polyurethane, endless foamed; F = flat gasket

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice.

2020-03-11