



ADVANTAGES

- Low pressure drop
- Robust and moisture resistant media
- Water resistant, rigid frame

Application	Replacement of gravimetric filters, Air Handling Units, Industrial processes and individual modules (reducing plant energy and IAQ improvement)
Type	Pleated Panel
Frame	ABS
Media	Synthetic
Separator	Hot-melt
Dimensions	Filter front dimensions according EN 15805
Rec. final pressure drop acc. EN 13053	Initial pressure drop + 100 Pa or initial pressure drop x3 (whichever is lower)
Max airflow	1,3 x nominal flow
Temperature max	70°C
RH. max	100%
Installation Options	Front and side access housings and frames are available



Type	EN779	ISO 16890	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Media area (m ²)	Weight (kg)
M-Pleat G	M5	Coarse 85%	287x592x48	1100/35	1,5	0,5
M-Pleat G	M5	Coarse 85%	592x592x48	2200/35	2,9	0,8
M-Pleat G	M5	Coarse 85%	592x592x96	2200/30	3,9	1,5
M-Pleat G	M5	Coarse 85%	287x592x96	1100/30	2	0,9

Other sizes available on request

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice.

2020-03-10